



**KEYWAYS ENGLISH
(In)**

SHAFT DIA.		W WIDTH	D _E DEPTH	
OVER	TO		STANDARD	SHALLOW
.50	.563	.125	.063	
.563	.875	.188	.094	
.875	1.250	.250	.125	
1.250	1.375	.312	.156	
1.375	1.750	.375	.188	
1.750	2.250	.500	.250	.125
2.250	2.750	.625	.313	.188
2.750	3.250	.750	.375	.188
3.250	3.750	.875	.438	.250
3.750	4.500	1.000	.500	.250
4.500	5.500	1.250	.625	.250
5.500	6.500	1.500	.750	.250
6.500	7.500	1.750	.750	.250
7.500	9.000	2.000	.750	.375

**KEYWAYS METRIC
(mm)**

SHAFT DIA.		W WIDTH	D _M DEPTH
OVER	TO		
6	8	2	1
8	10	3	1.4
10	12	4	1.8
12	17	5	2.3
17	22	6	2.8
22	30	8	3.3
30	38	10	3.3
38	44	12	3.3
44	50	14	3.8
50	58	16	4.3
58	65	18	4.4
65	75	20	4.9
75	85	22	5.4
85	95	25	5.4
95	110	28	6.4
110	130	32	7.4
130	150	36	8.4
150	170	40	9.4
170	200	45	10.4